

Euro DIN 15237 Elevator Bolts

BETTER BY DESIGN

Euro DIN 15237 Elevator Bolts Zinc Plated Steel / 304 Stainless Steel

APPLICATION

Used for fastening metal elevator buckets.

OVERVIEW

Euro DIN 15237 elevator bolts have a concave head and two lugs on the underside to prevent help rotation when tightening. Popular throughout Europe for the last 30 years, this fastening system is intended for the attachment of pressed steel elevator buckets incorporating recessed bolt holes. The recessed area surrounding the bolt hole is intended to accommodate the similarly domed surface under the bolt head. Because of this domed area under the bolt head, these bolts are not recommended for flat back plastic buckets, especially on thinner belts.

FEATURES

- ▶ ISO Grade 5.8 Steel (Exceeds DIN 15237)
- ▶ Concave Head & 2 Lugs Prevent Rotation During Tightening
- ▶ Allen Key Bolt Head Available for Steel Web Belts

HARDWARE

- ▶ Nuts, Washers & Spacers



FREE

Elevator & Conveyor Engineering Design Service

Take advantage of 4B's free, guaranteed worldwide technical support service from a team of material handling engineers specializing in the design and upgrade of bucket elevators and conveyors.

Whether you want a new elevator design, or just want to increase the capacity and performance of your existing elevator, our engineers can help.

Euro DIN 15237 Elevator Bolts

BETTER BY DESIGN

Metal Elevator Bucket Installation:

- Bolt, All Metal Lock Nut and Dome Washer for Recessed Bolt Hole Buckets (Image A)
- Bolt, All Metal Lock Nut and Flat Washer for Non-Recessed Bolt Hole Buckets (Image B)
- POZIDRIV® Head Recommended for Buckets on Steel Web Belting (Image C)



Image A



Image B



Image C

TECHNICAL SPECIFICATIONS

Euro DIN 15237 Elevator Bucket Bolts

Size (mm)	Zinc Plated Steel Part #	304 Stainless Part #	Head Diameter Ø (mm)	Max. Torque (in. lbs.) / (Nm)	Package Quantity	Package Weight (kg)
M6 x 20	EUM0620B	EUM0620B/304S	21	6 / 8	100	0.97
M6 x 25	EUM0625B	EUM0625B/304S	21	6 / 8	100	1.04
M6 x 30	EUM0630B	EUM0630B/304S	21	6 / 8	100	1.07
M7 x 20	EUM0720B	EUM0720B/304S	23	10 / 13	100	1.34
M7 x 25	EUM0725B	EUM0725B/304S	23	10 / 13	100	1.47
M7 x 30	EUM0730B	EUM0730B/304S	23	10 / 13	100	1.61
M7 x 35	EUM0735B	EUM0735B/304S	23	10 / 13	100	1.75
M8 x 20	EUM0820B	EUM0820B/304S	30	14 / 19	100	2.17
M8 x 25	EUM0825B	EUM0825B/304S	30	14 / 19	100	2.26
M8 x 30	EUM0830B	EUM0830B/304S	30	14 / 19	100	2.46
M8 x 35	EUM0835B	EUM0835B/304S	30	14 / 19	100	2.59
M8 x 40	EUM0840B	EUM0840B/304S	30	14 / 19	100	2.73
M8 x 45	EUM0845B	EUM0845B/304S	30	14 / 19	100	2.86
M8 x 50	EUM0850B	EUM0850B/304S	30	14 / 19	100	2.98
M10 x 25	EUM1025B	EUM1025B/304S	35	28 / 38	100	3.76
M10 x 30	EUM1030B	EUM1030B/304S	35	28 / 38	100	3.99
M10 x 35	EUM1035B	EUM1035B/304S	35	28 / 38	100	4.20
M10 x 40	EUM1040B	EUM1040B/304S	35	28 / 38	100	4.45
M10 x 45	EUM1045B	EUM1045B/304S	35	28 / 38	100	4.74
M10 x 50	EUM1050B	EUM1050B/304S	35	28 / 38	100	5.03
M12 x 40	EUM1240B	Not Available	42	49 / 66	100	6.68
M12 x 50	EUM1250B	Not Available	42	49 / 66	100	7.47
M12 x 60	EUM1260B	Not Available	42	49 / 66	100	8.30
M12 x 70	EUM1270B	Not Available	42	49 / 66	100	9.26

- Not Recommended for Flat Back Plastic Elevator Buckets
- Installed Bolt Torque Rating Dependent on Bucket & Belt Size

Information subject to change or correction. Sept 2014