

WARRANTY INFORMATION

1. EXCLUSIVE WRITTEN LIMITED WARRANTY

ALL PRODUCTS SOLD ARE WARRANTED BY THE COMPANY (4B COMPONENTS LIMITED, (4B) BRAIME ELEVATOR COMPONENTS LIMITED, AND (4B) S.E.T.E.M. Sarl) HEREIN AFTER REFERRED TO AS 4B TO THE ORIGINAL PURCHASER AGAINST DEFECTS IN WORKMANSHIP OR MATERIALS UNDER NORMAL USE FOR ONE (1) YEAR AFTER DATE OF PURCHASE FROM 4B. ANY PRODUCT DETERMINED BY 4B AT ITS SOLE DISCRETION TO BE DEFECTIVE IN MATERIAL OR WORKMANSHIP AND RETURNED TO A 4B BRANCH OR AUTHORIZED SERVICE LOCATION, AS 4B DESIGNATES, SHIPPING COSTS PREPAID, WILL BE, AS THE EXCLUSIVE REMEDY, REPAIRED OR REPLACED AT 4B'S OPTION.

2. DISCLAIMER OF IMPLIED WARRANTY

NO WARRANTY OR AFFIRMATION OF FACT, EXPRESSED OR IMPLIED, OTHER THAN AS SET FORTH IN THE EXCLUSIVE WRITTEN LIMITED WARRANTY STATEMENT ABOVE IS MADE OR AUTHORIZED BY 4B. 4B SPECIFICALLY DISCLAIMS ANY LIABILITY FOR PRODUCT DEFECT CLAIMS THAT ARE DUE TO PRODUCT MISUSE, ABUSE OR MISAPPLICATIONS, AS AUTHORIZED BY LAW, 4B SPECIFICALLY DISCLAIMS ALL WARRANTIES THAT THE PRODUCT IS FIT OR MERCHANTABLE FOR A PARTICULAR PURPOSE.

3. NO WARRANTY "BY SAMPLE OR EXAMPLE"

ALTHOUGH 4B HAS USED REASONABLE EFFORTS TO ACCURATELY ILLUSTRATE AND DESCRIBE THE PRODUCTS IN ITS CATALOGS, LITERATURE, AND WEBSITES, SUCH ILLUSTRATIONS AND DESCRIPTIONS ARE FOR THE SOLE PURPOSE OF PRODUCT IDENTIFICATION AND DO NOT EXPRESS OR IMPLY A WARRANTY AFFIRMATION OF FACT, OF ANY KIND OR A WARRANTY OR AFFIRMATION OF FACT THAT THE PRODUCTS WILL CONFORM TO THEIR RESPECTIVE ILLUSTRATIONS OR DESCRIPTIONS. 4B EXPRESSLY DISCLAIMS ANY WARRANTY OR AFFIRMATION OF FACT, EXPRESSED OR IMPLIED, OTHER THAN AS SET FORTH IN THE EXCLUSIVE WRITTEN LIMITED WARRANTY STATEMENT ABOVE, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

4. LIMITATION OF DAMAGES

ANY LIABILITY FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL, EXEMPLARY, OR PUNITIVE DAMAGES, OR FOR LOSS OF PROFIT WHETHER DIRECT OR INDIRECT, IS EXPRESSLY DISCLAIMED.



4B COMPONENTS

729 Sabrina Drive
East Peoria, Illinois 61611
USA
Tel: 309-698-5611
Fax: 309-698-5615
e-mail: 4b-usa@go4b.com
Web: www.go4b.com

4B BRAIME ELEVATOR COMPONENTS

Hunslett Road
Leeds, LS10 1JZ
England
Tel: +44 (0) 113 246 1800
Fax: +44 (0) 113 243 5021
e-mail: 4b-uk@go4b.com
Web: www.go4b.com

4B SETEM

9 Route de Corbie
80800 Lamotte Warfusée
France
Tel: +33 (0) 3 22 42 32 26
Fax: +33 (0) 3 22 42 37 33
e-mail: 4b-france@go4b.com
Web: www.go4b.com



M100

Stopped Motion Monitor
Décteur D'arrêt



INSTALLATION INSTRUCTIONS
MONTAGE ET INSTALLATION

TECHNICAL INFORMATION INFORMATION TECHNIQUE

WARNING: **NOT TO BE USED FOR BELT SLIP APPLICATIONS** Part No M1001V10F

General Specification**Spécifications Générales**

STOPSWITCH M100 -Stopped Motion Monitor.

STOPSWITCH M100 Détecteur d'arrêt de mouvement.

Features:

Inductive proximity sensor with fixed speed timer. Universal 24 to 240 Volt ac/dc supplies. No contact with moving machinery.
Self contained unit. Signals underspeed motion.
2 LED outputs monitor machine status.

Specification

Supply: 24 to 240 Volt ac/dc.
Fusing: Supply to be fused at 5A max.
Switching Capacity: 200mA max.
Saturation Voltage: 8 Volts max. (output ON)
Ambient Temperature: -25°C (-13°F) to +70°C (+158°F).
Output State: Normally Closed (Volt drop 8 Volts max.) above minimum input speed.
Normally Open (Leakage current 1.6mA max.) at stopped motion.
Sensing Range: 8 mm (5/16") maximum on ferrous metal at 25°C (77°F).
Input Pulse Range: 20 to 2000 ppm max.
Start-up Delay: 4 seconds.
Underspeed/Stopped Motion Trip Level: 4 seconds. The unit signals a 'stopped motion' condition if no inputs are received for a period of 4 seconds.
Enclosure: ISO threaded 18 mm by 1 mm pitch, moulded polycarbonate.
Protection: IP67 FM Approved Class II Div.1 Groups E, F and G.
Relative Humidity: 90% RH
LED Indicators: Red - "Target sensed". Green - "Closed circuit".
Connections: 2 wire, 2 metres (6ft) long leads. This can be extended, as with 2 wire lead.

Guarantee

The equipment is covered by a 12 month guarantee from the date of despatch. Any faults arising due to faulty materials or workmanship within the guarantee period will be corrected free of charge providing the equipment is returned to us freight paid.

Warning!

O.S.H.A requires that all exposed rotating shafts are provided with a full guard. Therefore, this device and its target must be equipped with a guard.

Caractéristiques

Détecteur de proximité inductif avec compteur d'impulsions. Alimentation universelle de 24 à 240 Volts ac/dc. Sans contact avec les appareils en mouvement. Appareil indépendant. Signale arrêt de mouvement. 2 voyants de rendement contrôlent les conditions de fonctionnement.

Spécifications

Alimentation: 24 à 240 Volt ac/dc.
Tension de déchet: 8 Volts maximum.
Température ambiante: moins 25°C a 70°C.
Conditions de marche: Circuit fermé sous tension. Circuit ouvert quand signal émis.
Portée nominale: 8 mm sur métaux ferreux à 25°C.
Plage d'utilisation: 20 à 2000 impulsions/minute.
Temporisation de mise en route: 4 secondes.
Seuil d'alarme: 4 secondes - l'appareil signale "arrêt mouvement" si aucune impulsion n'est reçue pendant cette période.
Enceinte: Polycarbonate moulé M 18 x 1 mm.
Protection: IP67. Approuvé FM Class II Div. 1 Groupes E, F et G
Humidité relative: 90% RH.
Voyants: Rouge - index détecté. Vert - sous tension.
Connection: Câble à 2 conducteurs de 2 mtr de long (plus long sur demande).

Garantie

Ce matériel est garanti contre tous vices de fabrication pour une période de 12 mois à compter de la date de livraison et sera remplacé sans frais. Celui-ci devra nous être retourné en 'port paye'.

Attention

Tous les arbres en mouvement exposés doivent être munis d'un dispositif protecteur.

Dear 4B Customer:

Congratulations on your purchase. 4B appreciates your business and is pleased you have chosen our products to meet your needs.

Please read in its entirety and understand the literature accompanying the product before you place the product into service. Please read the safety precautions carefully before operating the product. With each product you purchase from 4B, there are some basic but important safety considerations you must follow to be sure your purchase is permitted to perform its design function and operate properly and safely, giving you many years of reliable service. Please read and understand the Customer Safety Responsibilities listed below. Failure to follow this safety directive and the Operation Manuals and other material furnished or referenced, may result in serious injury or death.

SAFETY NOTICE TO OUR CUSTOMERS

- In order to maximize efficiency and safety, selecting the right equipment for each operation is vital. The proper installation of the equipment, and regular maintenance and inspection is equally important in continuing the proper operation and safety of the product. The proper installation and maintenance of all our products is the responsibility of the user unless you have asked 4B to perform these tasks.
- All installation and wiring must be in accordance with Local and National Electrical Codes and other standards applicable to your industry. (Please see the article "Hazard Monitoring Equipment Selection, Installation and Maintenance" at www.go4b.com.) The installation of the wiring should be undertaken by an experienced and qualified professional electrician. Failure to correctly wire any product and/or machinery can result in the product or machine failing to operate as intended, and can defeat its design function.
- Periodic inspection by a qualified person will help assure your 4B product is performing properly. 4B recommends a documented inspection at least annually and more frequently under high use conditions.
- Please see the last page of this manual for all warranty information regarding this product.

CUSTOMER SAFETY RESPONSIBILITIES**1. READ ALL LITERATURE PROVIDED WITH YOUR PRODUCT**

Please read all user, instruction and safety manuals to ensure that you understand your product operation and are able to safely and effectively use this product.

2. YOU BEST UNDERSTAND YOUR NEEDS

Every customer and operation is unique, and only you best know the specific needs and capabilities of your operation. Please call the 24-hour hotline at 309-698-5611 for assistance with any questions about the performance of products purchased from 4B. 4B is happy to discuss product performance with you at any time.

3. SELECT A QUALIFIED AND COMPETENT INSTALLER

Correct installation of the product is important for safety and performance. If you have not asked 4B to perform the installation of the unit on your behalf, it is critical for the safety of your operation and those who may perform work on your operation that you select a qualified and competent electrical installer to undertake the installation. The product must be installed properly to perform its designed functions. The installer should be qualified, trained, and competent to perform the installation in accordance with Local and National Electrical Codes, all relevant OSHA Regulations, as well as any of your own standards and preventive maintenance requirements, and other product installation information supplied with the product. You should be prepared to provide the installer with all necessary installation information to assist in the installation.

4. ESTABLISH AND FOLLOW A REGULAR MAINTENANCE AND INSPECTION SCHEDULE FOR YOUR 4B PRODUCTS

You should develop a proper maintenance and inspection program to confirm that your system is in good working order at all times. You will be in the best position to determine the appropriate frequency for inspection. Many different factors known to the user will assist you in deciding the frequency of inspection. These factors may include but are not limited to weather conditions; construction work at the facility; hours of operation; animal or insect infestation; and the real-world experience of knowing how your employees perform their jobs. The personnel or person you select to install, operate, maintain, inspect or perform any work whatsoever, should be trained and qualified to perform these important functions. Complete and accurate records of the maintenance and inspection process should be created and retained by you at all times.

5. RETAIN AND REFER TO THE OPERATION MANUAL FOR 4B'S SUGGESTED MAINTENANCE AND INSPECTION RECOMMENDATIONS

As all operations are different, please understand that your specific operation may require additional adjustments in the maintenance and inspection process essential to permit the monitoring device to perform its intended function. Retain the Operation Manual and other important maintenance and service documents provided by 4B and have them readily available for people servicing your 4B equipment. Should you have any questions, please call the 4B location who supplied the product or the 24-hour hotline number in the USA - 309-698-5611.

6. SERVICE REQUEST AND ONLINE PRODUCT REGISTRATION

If you have questions or comments about the operation of your unit or require the unit to be serviced please contact the 4B location who supplied the product or send your request via fax (309-698-5615), email (4b-usa@go4b.com), or call us via our 24-hour hotline number in the USA - 309-698-5611. Please have available product part numbers, serial numbers, and approximate date of installation. In order to assist you, after the product has been placed into service, complete the Online Product Registration section which is accessed via our website www.go4b.com

